

NX-1200A/1300A

5W VHF/UHF ANALOG PORTABLE RADIOS

NX-1200A/NX-1300A is efficient and functional 5W portable radios operate in analog FM. It is packed with features for intuitive operation and excellent performance. The model matrix includes basic and keypad variations, with or without a high-contrast backlit LCD. Other features include a 7-color LED indicator and KENWOOD 2-pin audio accessory connector. If you wish to transition to Digital capability, by purchasing a software option, DMR and Analog or NXDN and Analog mixed operation is available which gives you the freedom and flexibility to migrate at your own pace. All this comes in a tough, compact radio with great value and all weather reliability!

NXDN® **DMR** **DMR Auto Slot Select** **FleetSync®**



Standard Keypad & Basic Models

Features

Choose from direct & intuitive LCD with standard keypad or basic enclosures
Easy visible Display: 8-digit LCD models featuring high-contrast, white backlit LCD
Large 7-Color LED indicator on the top panel

- Selective Power-on LED
- Selective Call Alert LED
- Battery Level Indication
- Multi-status function indication

RF output power 5W both on VHF/UHF

Renowned KENWOOD Audio Quality: TX/RX audio profile with optimizable digital processor

- Audio Equalizer: Flat, High, Low
- Auto Gain Control: On, High, Low, Off
- Noise Suppressor
- Microphone type settings

Multiple Scan Functions; Dual Priority, Single Priority, Single Zone, Multi, Normal Scan

VOX & PTT –triggered Semi- VOX, Voice-operated TX

Emergency Function: Customizable Emergency Profile

Lone Worker

Max / Min Volume setting & Volume control

Voice Announcement

Remote Stun / Kill / Check

Front Panel Programming Mode (for Keypad model)

Electronic Serial Number (ESN)

MIL-STD-810 C/D/E/F/G

IP54 and IP55

Multi-protocol digital radio: Designed to operate under NXDN or DMR digital and FM analog protocols (Optional License required)

Analog – FM

FM Conventional Operation

FleetSync: PTT ID, Stun/Revive, Talk back, Selcall

MDC1200: PTT ID, Radio Inhibit/Uninhibit, Radio check, Emergency

QT / DQT, DTMF, 2-tone

Built-in Programmable Voice Inversion Scrambler (per channel)

Built-in Compressor (per channel)

Digital – NXDN® Mode (Optional License required)

FDMA – Very narrow 6.25 kHz & narrow 12.5 kHz bandwidths

NXDN Conventional Operation

Site Roaming

Digital / Analog Mixed mode

Group / Individual Call

Status / Short data, Paging Call

Remote Stun / Kill, Monitor, Check & Control

Digital Bit Scrambler

Late Entry

Over-the-Air Alias (OAA)

Digital – DMR Mode (Optional License required)

TDMA 2-slot 12.5 kHz bandwidth equivalent to 6.25 kHz very narrow bandwidth

DMR Tier II Conventional Operation

Site Roaming

DMR Auto Slot Select

Dual Slot Direct Mode

Digital / Analog Mixed mode

Call Interruption

Group / Individual Call

Status / Short data, Paging Call

Remote Stun / Kill, Monitor, Check & Control

Enhanced Encryption (ARC4)

Digital Bit Scrambler

Late Entry

Over-the-Air Alias (OAA)

Accessories

All accessories may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories.

<p>KNB-45L 2,000mAh/7.4V Li-Ion Battery Pack</p> 	<p>KSC-43K Dual Chemistry Fast Charger For the KNB 29N/45L/69L/82LCM</p> 	<p>KRA-26/ 27 VHF Helical Antenna UHF Whip Antenna</p> 	<p>KHS-26 Earbud In-line PTT Headset</p> 	<p>KBH-10 Belt Clip</p> 
<p>KNB-69L 2,550mAh/7.4V Li-Ion Battery Pack</p> 	<p>KVC-22 DC Vehicular Charger Adapter</p> 	<p>KRA-41/42 VHF/UHF Stubby Antenna</p> 	<p>KHS-27A D-Ring In-line PTT Headset</p> 	
<p>KSC-35SK Fast Charger For the KNB-45L/69L 82LCM (3-Hour)</p> 	<p>KRA-22/23 VHF/UHF Low Profile Helical Antenna</p> 	<p>KMC-45D Speaker Microphone</p> 	<p>KHS-31C C-Ring PTT Ear Hanger Headset</p> 	

Specifications

General	NX-1200A	NX-1300A
Frequencies Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Max. Channels per Radio Number of Zones Max. Channels per Zone	260 (64 for basic model) 128 (4 for basic model) 250 (16 for basic model)	
Channel Spacing Analog Digital	30" / 25" / 15 / 12.5 kHz 12.5 / 6.25 kHz	
Power Supply Battery Life KNB-45L (2000mAh) KNB-69L (2550mAh)	7.5 VDC ±20 % DMR Approx. 14.5 hours (15 hours for Basic model) Approx. 19 hours (19.5 hours for Basic model)	Analog/NXDN Approx. 11 hours (11.5 hours for Basic model) Approx. 14 hours (14.5 hours for Basic model)
Operating Temperature(Radio only)*	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability (-30 to +60°C; +25°C Ref.)	±0.5 ppm	
Antenna Impedance	50 Ω	
Dimensions Radio with KNB-45L/82LCM Radio with KNB-69L	(W x H x D) Projections Not Included 213 x 4.84 x 1.32 in (54 x 123 x 33.5 mm) 213 x 4.84 x 1.48 in (54 x 123 x 37.5 mm)	
Weight Radio Only Radio with KNB-45L/82LCM Radio with KNB-69L	(Basic model) (Standard keypad model) 5.64 oz (160 g) 6.17 oz (175 g) 9.88 oz (280 g) 10.41 oz (295 g) 10.41 oz (295 g) 10.93 oz (310 g)	
FCC ID Type 1 Type 2	K44501000 K44501101 K44501100	
IC Certification	282F-501000 282F-501100	

*1 25 / 30 kHz in VHF/UHF Bands excluding T-Band are not included in the models sold in the USA or US territories.
*2 Operating temperature specification for a Li-ion battery is -10°C to +60°C [14°F to +140°F].

Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications are subject change without notice, due to advancements in technology.

Receiver	NX-1200A	NX-1300A
Sensitivity NXDN* @ 6.25 kHz Digital (3% BER) NXDN* @ 12.5 kHz Digital (3% BER) DMR* @ 12.5 kHz Digital (1% BER) DMR* @ 12.5 kHz Digital (5% BER) Analog @ 12.5/25 kHz (12 dB SINAD)		0.18 μV 0.22 μV 0.25 μV 0.18 μV 0.20 μV / 0.24 μV
Selectivity Analog @ 12.5 / 25 kHz		68 dB / 74 dB
Intermodulation Distortion Spurious Rejection		70 dB 70 dB
Audio Distortion		7%
Audio Output Power		1 W / 12 Ω (Internal Output)

Transmitter	NX-1200A	NX-1300A
RF Power Output (High / Low)		5 W / 4 W / 1 W
Spurious Emission		-70 dB
FM Hum & Noise Analog @ 12.5 / 25 kHz		40 dB / 45 dB
Audio Distortion		2%
DMR Digital Protocol		ETSI TS 102 361-1, -2, -3
Emission Designator		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D, 7K60FXD, 7K60F7W

FleetSync® is a registered trademark of JVCケンウッド Corporation in the United States and/or other countries.
NXDN® is a trademark of JVCケンウッド Corporation and Icom Inc.
NEXEDGE® is a registered trademark of JVCケンウッド Corporation.
All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	5001/Procedure I	5002/Procedure I, II	5003/Procedure I, II	5004/Procedure I, II	5005/Procedure I, II
High Temperature	5011/Procedure I, II	5012/Procedure I, II	5013/Procedure I, II	5014/Procedure I, II	5015/Procedure I, II
Low Temperature	5021/Procedure I	5022/Procedure I, II	5023/Procedure I, II	5024/Procedure I, II	5025/Procedure I, II
Temperature Shock	5031/Procedure I	5032/Procedure I	5033/Procedure I	5034/Procedure I, II	5035/Procedure I
Solar Radiation	5051/Procedure I	5052/Procedure I	5053/Procedure I	5054/Procedure I	5055/Procedure I
Rain*	5061/Procedure I, II	5062/Procedure I, II	5063/Procedure I, II	5064/Procedure I, III	5065/Procedure I, III
Humidity	5071/Procedure I, II	5072/Procedure II, III	5073/Procedure II, III	5074	5075/Procedure II
Salt Fog	5091/Procedure I	5092/Procedure I	5093/Procedure I	5094	5095
Dust	5101/Procedure I	5102/Procedure I	5103/Procedure I	5104/Procedure I, III	5105/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV

International Protection Standard
 Dust & Water Protection* IP54/55* To meet IP54/55, the 2-pin connector cover has to be connected on the radio or the locking bracket has to be attached to the external speaker microphone.

JVCケンWOOD USA Corporation
 Communications Sector Headquarters
 1440 Corporate Drive | Irving, TX 75038
 Order Administration/Distribution
 P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745
www.kenwood.com/usa

JVCケンWOOD Canada Inc.
 Sede central y distribución canadiense
 6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca

KENWOOD Communications
 Global Website

comms.kenwood.com


 ISO9001 Registered
 Communications Systems Business Unit
 JVCケンWOOD Corporation